NSN 5950-00-252-3461

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-252-3461

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 8.810 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.880 inches single mounting facility single center group |
| Overall Width: |
| 4.880 inches |
| Mounting Hole Diameter: |
| 0.217 inches single group and 0.223 inches single group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Three phase to three phase single component |
| Winding Shielding Method: |
| Internal shield grounded to core single component |
| Body Length: |
| 9.880 inches |
| Body Width: |
| 3.880 inches |
| Body Height: |
| 6.000 inches |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Terminal Type And Quantity: |
| 12 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A050k0 |

A058b0