## NSN 5950-00-253-4109

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-253-4109

| Reliability Indicator:  |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.750 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 3.625 inches single mounting facility single center group                 |
| Frequency Rating:   |
| 50.0 hertz or 60.0 hertz single component                                 |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Body Length:  |
| 4.500 inches  |
| Body Width:   |
| 3.062 inches  |
| Body Height:  |
| 4.609 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Flange and unthreaded hole single group                                   |
| Winding Function And Quantity:  |
| 1 primary and 1 secondary single component                                |
| Winding Operating Current:  |
| 3.23 amperes ac single component single secondary                         |
| Winding Operating Voltage:  |
| 220.00 ac volts single component single primary                           |
| Terminal Type And Quantity:   |
| 10 threaded stud  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <b></b>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A058b0  |