## NSN 5950-00-253-7083

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-253-7083

Reliability Indicator:
Not established
Overall Height:
3.344 inches
Frequency Rating:
55.0 hertz single component and 65.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Body Length:
1.500 inches
Body Width:
1.313 inches
Body Height:
2.469 inches
Distance Between Mounting Facility Centers:
1.062 inches single mounting facility single center group
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Winding Operating Current:
750.0 milliamperes ac single component single secondary
Winding Operating Voltage:
115.00 ac volts single component single primary3.00 ac volts single component single secondary and 4.50 ac volts single component
single secondary and 6.30 ac volts single component single secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
6 standoff, solder lug
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5950-00-253-7083

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0