# NSN 5950-00-254-0028

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-254-0028

Reliability	Indicator:
-------------	------------

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.906 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.688 inches single mounting facility single center group

#### Frequency Rating:

60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to core single component

**Body Length:** 

2.562 inches

**Body Width:** 

2.250 inches

**Body Height:** 

3.812 inches

#### **Inclosure Type:**

Hermetically sealed

### **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded stud single group

#### **Winding Function And Quantity:**

1 primary single component and 2 secondary single component

#### Thready Qty Per Inch (tpi):

32 single group

## Thread Size:

0.138 inches single group

#### **Winding Operating Current:**

2.0 milliamperes ac single component all secondary

#### **Winding Operating Voltage:**

120.00 ac volts single component single primary and 250.00 ac volts single component all secondary140.00 ac volts single component single primary and 160.00 ac volts single component single primary and 184.00 ac volts single component single primary and 212.00 ac volts single component single primary

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

12 tab, solder lug

# Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5950-00-254-0028

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0