# NSN 5950-00-255-2232

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-255-2232

# **Reliability Indicator:**

Not establishednot established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

4.625 inches single mounting facility single center group4.625 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

#### **Overall Height:**

7.500 inches 7.500 inches

#### Frequency Rating:

60.0 hertz single component60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

#### **Body Length:**

4.625 inches 4.625 inches

#### **Body Width:**

4.000 inches 4.000 inches

#### **Inclosure Type:**

Fully enclosedfully enclosed

# **Mounting Facility Quantity:**

4 single group4 single group

# **Mounting Method:**

Threaded hole single groupthreaded hole single group

#### **Winding Function And Quantity:**

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

# Thready Qty Per Inch (tpi):

24 single group24 single group

# Thread Size:

0.190 inches single group0.190 inches single group

#### **Winding Operating Current:**

2.5 amperes ac single component 1st secondary

# **Winding Operating Voltage:**

7.50 ac volts single component 1st secondary

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

6 standoff, threaded stud and 2 threaded stud

#### Shelf Life:

N/a

# **Unit Of Measure:**

#### **Demilitarization:**

No

# NSN 5950-00-255-2232

Power Transformer - Page 2 of 2



Fiig:

A058b0