

View Online at <https://aerobasegroup.com/nsn/5950-00-256-1180>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

8.750 inches single mounting facility single center group8.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

5.250 inches single mounting facility single center group5.250 inches single mounting facility single center group

Frequency Rating:

55.0 hertz single component and 55.0 hertz single component and 65.0 hertz single component65.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

10.000 inches 10.000 inches

Body Width:

6.500 inches 6.500 inches

Body Height:

7.000 inches 7.000 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

2 primary single component and 2 primary single component and 3 secondary single component3 secondary single component

Thready Qty Per Inch (tpi):

40 single group40 single group

Thread Size:

0.112 inches single group0.112 inches single group

Winding Operating Current:

3.0 amperes ac single component 2nd secondary

Winding Operating Voltage:

94.00 ac volts single component 1st primary and 5.00 ac volts single component 1st secondary99.00 ac volts single component 1st primary and 104.00 ac volts single component 1st primary and 115.00 ac volts single component 1st primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 standoff insulator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0