NSN 5950-00-256-2351

Radio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-256-2351

| view Online at https://aerobasegroup.com/nsn/5950-00-2 | 56-2351 |
|---|-------------|
| Reliability Indicator: | |
| Not established | |
| Turn Quantity: | |
| 3 single component single primary | |
| Inductance Rating: | |
| 0.009 microhenries single component single primary | |
| Coil Form Type: | |
| Hollow single component | |
| Adjustment Device Drive Type: | |
| Slotted screw single component | |
| Body Length: | |
| 2.250 inches | |
| Body Width: | |
| 1.062 inches | |
| Body Height: | |
| 0.562 inches | |
| Distance Between Mounting Facility Centers: | |
| 0.750 inches single mounting facility single center group | |
| Inclosure Type: | |
| Open | |
| Mounting Facility Quantity: | |
| 2 single group | |
| Mounting Method: | |
| Threaded hole single group | |
| Rating Method: | |
| Winding turns single component single primary | |
| Winding Function And Quantity: | |
| 1 primary single component | |
| Thready Qty Per Inch (tpi): | |
| 40 single group | |
| Thread Size: | |
| 0.112 inches single group | |
| Winding Conductor Size: | |
| 0.03196 inches american wire gage single component sin | gle primary |
| Adjustment Method And Quantity: | |
| 1 adjustable core single component | |
| Thread Series Designator: | |
| Unf single group | |
| Terminal Type And Quantity: | |
| 3 tab, solder lug | |
| Shelf Life: | |
| | |

N/a

NSN 5950-00-256-2351

Radio Frequency Transformer - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A058b0