

View Online at <https://aerobasegroup.com/nsn/5950-00-256-8688>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.182 inches single mounting facility single center group3.182 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.125 inches single mounting facility single center group3.125 inches single mounting facility single center group

**Overall Height:**

5.688 inches 5.688 inches

**Frequency Rating:**

50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Body Length:**

4.125 inches 4.125 inches

**Body Width:**

4.875 inches 4.875 inches

**Body Height:**

5.000 inches 5.000 inches

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

**Thready Qty Per Inch (tpi):**

20 single group20 single group

**Thread Size:**

0.250 inches single group0.250 inches single group

**Winding Operating Current:**

3.0 amperes ac single component 2nd secondary

**Winding Operating Voltage:**

610.00 ac volts single component 1st secondary230.00 ac volts single component single primary5.00 ac volts single component 2nd secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

10 standoff insulator

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0