

View Online at <https://aerobasegroup.com/nsn/5950-00-256-8971>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.875 inches single mounting facility single center group

Frequency Rating:

45.0 hertz single component and 65.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

3.500 inches

Body Width:

2.875 inches

Body Height:

4.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

30.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

130.00 ac volts single component 1st secondary 65.00 ac volts single component 2nd secondary and 80.00 ac volts single component 2nd secondary and 150.00 ac volts single component 2nd secondary and 290.00 ac volts single component 2nd secondary and 360.00 ac volts single component 2nd secondary and 375.00 ac volts single component 2nd secondary and 440.00 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 solder stud

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A058b0