## NSN 5950-00-257-1610

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-257-1610

## **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.500 inches single mounting facility single center group

#### **Overall Height:**

4.875 inches

#### **Overall Width:**

4.375 inches

#### Frequency Rating:

60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure single component

#### **Body Length:**

4.438 inches

#### **Inclosure Type:**

Fully enclosed

## **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded stud single group

## **Winding Function And Quantity:**

1 primary single component and 4 secondary single component

## Thready Qty Per Inch (tpi):

32 single group

## Thread Size:

0.190 inches single group

## **Winding Operating Current:**

600.0 milliamperes ac single component 1st secondary

## **Winding Operating Voltage:**

6.30 ac volts single component all secondary115.00 ac volts single component single primary

#### **Special Features:**

6.3 v.22 amp winding has 4 extra terminals

## **Thread Series Designator:**

Unf single group

### **Terminal Type And Quantity:**

16 standoff, solder lug

## Shelf Life:

N/a

# NSN 5950-00-257-1610

Power Transformer - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A058b0