

View Online at <https://aerobasegroup.com/nsn/5950-00-257-1615>

Reliability Indicator:

Not establishednot establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.422 inches single mounting facility single center group and 1.422 inches single mounting facility single center group and 1.422 inches single mounting facility single center group and 1.454 inches single mounting facility single center group1.454 inches single mounting facility single center group1.454 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.422 inches single mounting facility single center group and 1.422 inches single mounting facility single center group and 1.422 inches single mounting facility single center group and 1.454 inches single mounting facility single center group1.454 inches single mounting facility single center group1.454 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single componentinternal shield grounded to core single componentinternal shield grounded to core single component

Body Length:

Between 2.203 inches and 2.203 inches and 2.203 inches and 2.235 inches 2.235 inches 2.235 inches

Body Width:

Between 2.078 inches and 2.078 inches and 2.078 inches and 2.110 inches 2.110 inches 2.110 inches

Body Height:

Between 2.734 inches and 2.734 inches and 2.734 inches and 2.766 inches 2.766 inches 2.766 inches

Inclosure Type:

Hermetically sealedhermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component3 secondary single component

Thread Size:

0.164 inches single group0.164 inches single group

Winding Operating Current:

209.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

55.00 ac volts single component 2nd secondary110.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 turret

Shelf Life:

N/a

Fiig:

A058b0