

View Online at <https://aerobasegroup.com/nsn/5950-00-257-1652>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.250 inches single mounting facility single center group4.250 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.625 inches single mounting facility single center group4.625 inches single mounting facility single center group

**Frequency Rating:**

58.0 hertz single component and 58.0 hertz single component and 62.0 hertz single component62.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

**Body Length:**

5.500 inches 5.500 inches

**Body Width:**

4.875 inches 4.875 inches

**Body Height:**

5.125 inches 5.125 inches

**Inclosure Type:**

Openopen

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

**Thready Qty Per Inch (tpi):**

20 single group20 single group

**Thread Size:**

0.250 inches single group0.250 inches single group

**Winding Operating Current:**

20.0 milliamperes ac single component single secondary

**Winding Operating Voltage:**

800.00 ac volts single component single secondary115.00 ac volts single component single primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0