

View Online at <https://aerobasegroup.com/nsn/5950-00-257-1652>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.250 inches single mounting facility single center group4.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.625 inches single mounting facility single center group4.625 inches single mounting facility single center group

Frequency Rating:

58.0 hertz single component and 58.0 hertz single component and 62.0 hertz single component62.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

Body Length:

5.500 inches 5.500 inches

Body Width:

4.875 inches 4.875 inches

Body Height:

5.125 inches 5.125 inches

Inclosure Type:

Openopen

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thready Qty Per Inch (tpi):

20 single group20 single group

Thread Size:

0.250 inches single group0.250 inches single group

Winding Operating Current:

20.0 milliamperes ac single component single secondary

Winding Operating Voltage:

800.00 ac volts single component single secondary115.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0