

View Online at <https://aerobasegroup.com/nsn/5950-00-257-3213>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

3.938 inches 3.938 inches

Body Width:

3.938 inches 3.938 inches

Body Height:

5.000 inches 5.000 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

Thready Qty Per Inch (tpi):

20 single group20 single group

Thread Size:

0.250 inches single group0.250 inches single group

Winding Operating Current:

2.5 amperes ac single component 2nd secondary

Winding Operating Voltage:

6.50 ac volts single component 2nd secondary and 6.66 ac volts single component 2nd secondary and 6.82 ac volts single component 2nd secondary and 6.98 ac volts single component 2nd secondary and 7.15 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 standoff, threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0