NSN 5950-00-257-3223

Power Autotransformer Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-257-3223

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 1.875 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.500 inches single mounting facility single center group Frequency Rating:
Center To Center Distance Between Mounting Facilities Parallel To Length: 1.875 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.500 inches single mounting facility single center group
 1.875 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.500 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width: 1.500 inches single mounting facility single center group
1.500 inches single mounting facility single center group
Fraguency Pating:
Frequency Rading.
60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
2.375 inches
Body Width:
2.000 inches
Body Height:
3.000 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary, fixed autotransformer type single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Winding Operating Current:
200.0 milliamperes ac single component single primary output
Winding Operating Voltage:
78.00 ac volts single component single primary output
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
3 wire hook
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

NSN 5950-00-257-3223

Power Autotransformer Transformer - Page 2 of 2



Fiig:

A058b0