

View Online at <https://aerobasegroup.com/nsn/5950-00-257-9491>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

1.930 inches

Body Width:

1.820 inches

Body Height:

2.750 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

0.5 milliamperes ac single component single secondary and 200.0 milliamperes ac single component single secondary

Winding Operating Voltage:

1.50 ac kilovolts single component single secondary and 1.515 ac kilovolts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

1 wire lead w/clamp and 6 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0