

View Online at <https://aerobasegroup.com/nsn/5950-00-259-5774>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

8.062 inches single mounting facility single center group8.062 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.375 inches single mounting facility single center group4.375 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component and 50.0 hertz single component and 60.0 hertz single component60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core and brought out to terminal single componentinternal shield grounded to core and brought out to terminal single component

**Body Length:**

8.500 inches 8.500 inches

**Body Width:**

6.500 inches 6.500 inches

**Body Height:**

5.540 inches 5.540 inches

**Inclosure Type:**

Partially enclosed, double shellpartially enclosed, double shell

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 9 secondary single component9 secondary single component

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

6.0 amperes dc single component 4th secondary

**Winding Operating Voltage:**

8.00 dc volts single component 3rd secondary25.00 dc volts single component 4th secondary120.00 ac volts single component single primary and 127.00 ac volts single component single primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

26 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0