

View Online at <https://aerobasegroup.com/nsn/5950-00-262-2249>

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.625 inches single mounting facility single center group

Mounting Hole Diameter:

0.406 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

9.406 inches

Body Width:

7.938 inches

Body Height:

12.250 inches

End Application:

Utarawa class lha, kidd class ddg, ticonderoga class cg (47), nimitz class cvn, virginia class cgn (41), forrestal class cv, los angeles class ssn (688), wasp class lhd, spruance class dd (963). An/srn-2 (v) navigation radio set.

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

83.5 amperes ac single component single secondary

Winding Power Rating:

10.0 k1lovolt-amperes single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

450.00 ac pounds per hour wet single component single primary

Special Features:

Weapon system essential

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0

Mil-std (military Standard):

Mil-t-17221 spec.