

View Online at <https://aerobasegroup.com/nsn/5950-00-262-3218>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.940 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

3.190 inches

Body Width:

1.560 inches

Body Height:

2.440 inches

Maximum Operating Temp:

100.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

1.0 amperes dc single component 4th secondary

Winding Power Rating:

2.0 watts single component single primary

Winding Operating Voltage:

17.00 ac volts single component 1st secondary15.09 ac volts single component 3rd secondary15.09 ac volts single component 2nd secondary

Special Features:

6secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

22 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0