## NSN 5950-00-263-1022

Audio Frequency Transformer - Page 1 of 2



| Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 1.312 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.062 inches single mounting facility single center group Transformer Function: Output Impedance Rating In Ohms: 0.195 single component single secondary and 0.780 single component single secondary and 12.500 single component single secondary and 50.000 single component single secondary and 200.000 single component single secondary Frequency Rating: 0.000 single component and 4.0 kilohertz single component Maximum Transformer Power Rating: 080.0 heritz single component Maximum Transformer Power Rating: 080.0 heritz single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 2.094 inches Body Width: 1.781 inches Body Width: 1.781 inches Body Wighth: 3.250 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 4 primary single component and 1 secondary single component Special Features: Case metal material Terminal Type And Quantity: 8 tab., solder lug 8 shell Life: N/a             | View Online at https://aerobasegroup.com/nsn/5950-00-263-1022                                                                    |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Center To Center Distance Between Mounting Facilities Parallel To Length: 1.312 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.052 inches single mounting facility single center group Transformer Function: Output Impedance Rating In Ohms: In 1955 single component single secondary and 0.780 single component single secondary and 12.500 single component single secondary and 50.000 single component single secondary and 50.000 single component single secondary and 50.000 single component single secondary Proquency Rating: 300.0 hertz single component and 4.0 kilohertz single component Maximum Transformer Power Rating: 800.0 milliwatts single component Primary To Secondary Turn Ratio: 4.48 to 1 single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 2.094 inches Body Width: 1.781 inches Body Height: 3.250 inches Inclosure Type: Hermetically sealed Mounting Method: Threaded stud single group Winding Function And Quantity: 4 single group Winding Function And Quantity: 9 trimary single component and 1 secondary single component Special Features: Case metal material Terminal Type And Quantity: 8 tab., solder lug Shell Life: N/a | Reliability Indicator:                                                                                                           |
| 1.312 inches single mounting facility single center group  Center To Center Distance Between Mounting Facilities Parallel To Width: 1.062 inches single mounting facility single center group  Transformer Function: Output  Impedance Rating In Ohms: 0.195 single component single secondary and 0.780 single component single secondary and 12.500 single component single secondary and 50.000 single component single secondary and 50.000 single component single secondary  Frequency Rating: 300.0 hertz single component and 4.0 kilohertz single component Maximum Transformer Power Rating: 300.0 milliwatts single component  Primary To Secondary Turn Ratio: 4.48 to 1 single component  Winding Shielding Method: Internal shield grounded to inclosure single component  Body Length: 2.094 inches  Body Width: 1.781 inches  Body Width: 1.781 inches  Mounting Facility Quantity: 4 single group  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 9 primary single component and 1 secondary single component  Special Features: Case metal material  Terminal Type And Quantity: 8 single softer lug  Sheft Life: No                                                                                                       | Not established                                                                                                                  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  1.062 inches single mounting facility single center group  Transformer Function:  Output  Impedance Rating In Ohms:  0.195 single component single secondary and 0.780 single component single secondary and 12.500 single component single secondary and 50.000 single component single secondary and 50.000 single component single secondary and 50.000 single component single secondary  Frequency Rating:  300.00 hertz single component and 4.0 kilohertz single component  Maximum Transformer Power Rating:  800.0 milliwatts single component  Primary To Secondary Turn Ratio:  4.48 to 1 single component  Winding Shielding Method:  Internal shield grounded to inclosure single component  Body Length:  2.094 inches  Body Width:  1.781 inches  Body Height:  3.250 inches  Inclosure Type:  Hermetically sealed  Mounting Facility Quantity:  4 single group  Mounting Method:  Threaded stud single group  Winding Function And Quantity:  4 primary single component and 1 secondary single component  Special Features:  Case metal material  Terminal Type And Quantity:  8 tab., solder lug  Sheff Life:  N/a                                                                                                        | Center To Center Distance Between Mounting Facilities Parallel To Length:                                                        |
| 1.062 inches single mounting facility single center group Transformer Function: Output Impedance Rating in Ohms: 0.195 single component single secondary and 0.780 single component single secondary and 12.500 single component single secondary and 50.000 single component single secondary and 50.000 single component single secondary and 50.000 single component single secondary Frequency Rating: 300.0 heriz single component and 4.0 kilohertz single component Maximum Transformer Power Rating: 800.0 milliwatts single component Primary To Secondary Turn Ratio: 4.48 to 1 single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 2.094 inches Body Width: 1.781 inches Body Height: 3.250 inches Inclosur Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Special Features: Case metal material Terminal Type And Quantity: 8 shot, solder lug Shelf Life: No                                                                                                                                                                          | 1.312 inches single mounting facility single center group                                                                        |
| Transformer Function: Output Impedance Rating In Ohms: 0.195 single component single secondary and 0.780 single component single secondary and 12.500 single component single secondary and 50.000 single component single secondary and 50.000 single component single secondary Frequency Rating: 300.0 hertz single component and 4.0 kilohertz single component Maximum Transformer Power Rating: 800.0 milliwatts single component Primary To Secondary Turn Ratio: 4.48 to 1 single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 2.094 inches Body Width: 1.781 inches Body Height: 3.250 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Special Features: Case metal material Terminal Type And Quantity: 8 tab, solder lug Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                       | Center To Center Distance Between Mounting Facilities Parallel To Width:                                                         |
| Output  Impedance Rating In Ohms: 0.195 single component single secondary and 0.780 single component single secondary and 12.500 single component single secondary and 50.000 single component single secondary and 200.000 single component single secondary Frequency Rating: 300.0 hertz single component and 4.0 kilohertz single component Maximum Transformer Power Rating: 800.0 milliwatts single component Primary To Secondary Turn Ratio: 4.48 to 1 single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 2.094 inches Body Width: 1.781 inches Body Height: 3.250 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Special Features: Case metal material Terminal Type And Quantity: 8 tab, solder lug Shiel Life: N/a                                                                                                                                                                                                                                                                                                                                                                                           | 1.062 inches single mounting facility single center group                                                                        |
| Impedance Rating In Ohms:  0.195 single component single secondary and 0.780 single component single secondary and 12.500 single component single secondary and 50.000 single component single secondary and 200.000 single component single secondary  Frequency Rating: 300.0 hertz single component and 4.0 kilohertz single component  Maximum Transformer Power Rating: 300.0 milliwatts single component  Primary To Secondary Turn Ratio: 4.48 to 1 single component  Winding Shielding Method: Internal shield grounded to inclosure single component  Body Length: 2.094 inches  Body Width: 1.781 inches  Body Height: 3.250 inches Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Special Features: Case metal material  Treminal Type And Quantity: 8 tels, solder lug  Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                     | Transformer Function:                                                                                                            |
| 0.195 single component single secondary and 0.780 single component single secondary and 12.500 single component single secondary and 50.000 single component single secondary and 50.000 single component single secondary and 50.000 single component single secondary  Frequency Rating: 300.0 hetrz single component and 4.0 kilohertz single component  Maximum Transformer Power Rating: 800.0 milliwatts single component  Primary To Secondary Turn Ratio: 4.48 to 1 single component  Winding Shielding Method: Internal shield grounded to inclosure single component  Body Length: 2.094 inches  Body Width: 1.781 inches  Body Height: 3.250 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Facility Quantity: 5 single group  Winding Function And Quantity: 7 primary single component and 1 secondary single component  Special Features: Case metal material  Terminal Type And Quantity: 8 tab, solder lug  Shell Life: N/a                                                                                                                                                                                                                                                                                                                        | Output                                                                                                                           |
| and 50.000 single component single secondary and 200.000 single component single secondary  Frequency Rating: 300.0 hertz single component and 4.0 kilohertz single component  Maximum Transformer Power Rating: 800.0 milliwatts single component  Primary To Secondary Turn Ratio: 4.48 to 1 single component  Winding Shielding Method: Internal shield grounded to inclosure single component  Body Length: 2.094 inches Body Width: 1.781 inches Body Height: 3.250 inches Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Special Features: Case metal material  Terminal Type And Quantity: 8 tab, solder lug  Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Impedance Rating In Ohms:                                                                                                        |
| Frequency Rating: 300.0 hertz single component and 4.0 kilohertz single component  Maximum Transformer Power Rating: 800.0 milliwatts single component  Primary To Secondary Turn Ratio: 4.48 to 1 single component  Winding Shielding Method: Internal shield grounded to inclosure single component  Body Length: 2.094 inches  Body Width: 1.781 inches Body Height: 3.250 inches Inclosure Type: Hormetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Special Features: Case metal material  Terminal Type And Quantity: 8 tab, solder lug  Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 0.195 single component single secondary and 0.780 single component single secondary and 12.500 single component single secondary |
| Maximum Transformer Power Rating: 800.0 hertz single component Primary To Secondary Turn Ratio: 4.48 to 1 single component Winding Shielding Method: Internal shield grounded to inclosure single component  Body Length: 2.094 inches Body Width: 1.781 inches Body Height: 3.250 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Special Features: Case metal material Terminal Type And Quantity: 8 tab, solder lug Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | and 50.000 single component single secondary and 200.000 single component single secondary                                       |
| Maximum Transformer Power Rating: 800.0 milliwatts single component Primary To Secondary Turn Ratio: 4.48 to 1 single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 2.094 inches Body Width: 1.781 inches Body Height: 3.250 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Special Features: Case metal material Terminal Type And Quantity: 8 tab, solder lug Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Frequency Rating:                                                                                                                |
| 800.0 milliwatts single component  Primary To Secondary Turn Ratio: 4.48 to 1 single component  Winding Shielding Method: Internal shield grounded to inclosure single component  Body Length: 2.094 inches  Body Width: 1.781 inches  Body Height: 3.250 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Special Features: Case metal material  Terminal Type And Quantity: 8 tab, solder lug  Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 300.0 hertz single component and 4.0 kilohertz single component                                                                  |
| Primary To Secondary Turn Ratio: 4.48 to 1 single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 2.094 inches Body Width: 1.781 inches Body Height: 3.250 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Special Features: Case metal material Terminal Type And Quantity: 8 tab, solder lug Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Maximum Transformer Power Rating:                                                                                                |
| 4.48 to 1 single component  Winding Shielding Method: Internal shield grounded to inclosure single component  Body Length: 2.094 inches  Body Width: 1.781 inches  Body Height: 3.250 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Special Features: Case metal material  Terminal Type And Quantity: 8 tab, solder lug  Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 800.0 milliwatts single component                                                                                                |
| Winding Shielding Method: Internal shield grounded to inclosure single component  Body Length: 2.094 inches Body Width: 1.781 inches Body Height: 3.250 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Special Features: Case metal material Terminal Type And Quantity: 8 tab, solder lug Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Primary To Secondary Turn Ratio:                                                                                                 |
| Internal shield grounded to inclosure single component  Body Length: 2.094 inches  Body Width: 1.781 inches  Body Height: 3.250 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Special Features: Case metal material  Terminal Type And Quantity: 8 tab, solder lug  Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 4.48 to 1 single component                                                                                                       |
| Body Length: 2.094 inches Body Width: 1.781 inches Body Height: 3.250 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Special Features: Case metal material Terminal Type And Quantity: 8 tab, solder lug Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Winding Shielding Method:                                                                                                        |
| 2.094 inches  Body Width: 1.781 inches  Body Height: 3.250 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Special Features: Case metal material  Terminal Type And Quantity: 8 tab, solder lug  Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Internal shield grounded to inclosure single component                                                                           |
| Body Width:  1.781 inches  Body Height: 3.250 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Special Features: Case metal material  Terminal Type And Quantity: 8 tab, solder lug  Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Body Length:                                                                                                                     |
| 1.781 inches  Body Height: 3.250 inches Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Special Features: Case metal material  Terminal Type And Quantity: 8 tab, solder lug  Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 2.094 inches                                                                                                                     |
| Body Height: 3.250 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Special Features: Case metal material Terminal Type And Quantity: 8 tab, solder lug Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Body Width:                                                                                                                      |
| 3.250 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Special Features: Case metal material Terminal Type And Quantity: 8 tab, solder lug Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 1.781 inches                                                                                                                     |
| Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Special Features: Case metal material Terminal Type And Quantity: 8 tab, solder lug Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Body Height:                                                                                                                     |
| Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Special Features: Case metal material  Terminal Type And Quantity: 8 tab, solder lug  Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 3.250 inches                                                                                                                     |
| Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Special Features: Case metal material  Terminal Type And Quantity: 8 tab, solder lug  Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Inclosure Type:                                                                                                                  |
| 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Special Features: Case metal material  Terminal Type And Quantity: 8 tab, solder lug  Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Hermetically sealed                                                                                                              |
| Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Special Features: Case metal material Terminal Type And Quantity: 8 tab, solder lug Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Mounting Facility Quantity:                                                                                                      |
| Threaded stud single group  Winding Function And Quantity:  1 primary single component and 1 secondary single component  Special Features:  Case metal material  Terminal Type And Quantity:  8 tab, solder lug  Shelf Life:  N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 4 single group                                                                                                                   |
| Winding Function And Quantity:  1 primary single component and 1 secondary single component  Special Features:  Case metal material  Terminal Type And Quantity:  8 tab, solder lug  Shelf Life:  N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Mounting Method:                                                                                                                 |
| 1 primary single component and 1 secondary single component  Special Features: Case metal material  Terminal Type And Quantity: 8 tab, solder lug  Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Threaded stud single group                                                                                                       |
| Special Features: Case metal material Terminal Type And Quantity: 8 tab, solder lug Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Winding Function And Quantity:                                                                                                   |
| Case metal material  Terminal Type And Quantity: 8 tab, solder lug  Shelf Life:  N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 1 primary single component and 1 secondary single component                                                                      |
| Terminal Type And Quantity: 8 tab, solder lug Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Special Features:                                                                                                                |
| 8 tab, solder lug Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Case metal material                                                                                                              |
| Shelf Life: N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Terminal Type And Quantity:                                                                                                      |
| N/a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 8 tab, solder lug                                                                                                                |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Shelf Life:                                                                                                                      |
| Unit Of Measure:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | N/a                                                                                                                              |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Unit Of Measure:                                                                                                                 |

No

Demilitarization:

## NSN 5950-00-263-1022

Audio Frequency Transformer - Page 2 of 2



Fiig:

A058b0