

View Online at <https://aerobasegroup.com/nsn/5950-00-263-1029>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.125 inches single mounting facility single center group

Mounting Slot Width:

0.406 inches single group

Impedance Rating In Ohms:

8335.0 single component single secondary

Frequency Rating:

100.0 hertz single component and 1.0 kilohertz single component

Maximum Transformer Power Rating:

250.0 watts single component

Primary To Secondary Turn Ratio:

1 to 1-1/2 single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

10.750 inches

Body Width:

7.312 inches

Body Height:

6.375 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

265.0 milliamperes dc single component single secondary

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0