## NSN 5950-00-264-5583

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-264-5583

Reliability Indicator: Not established Inductance Type: Fixed Inductance Rating: 600.00 microhenries single component single winding Frequency Rating: 800.0 hertz single component Body Length: 0.600 inches Body Outside Diameter: 1.188 inches Maximum Operating Temp: 130.0 degrees celsius Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Winding Operating Current: 750.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.250 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a Unit Of Measure:	Not established Inductance Type: Fixed Inductance Rating: 600.00 microhenries single component single winding Frequency Rating: 800.0 hertz single component Body Length: 0.600 inches Body Outside Diameter: 1.188 inches Maximum Operating Temp: 130.0 degrees celsius Winding Quantity: 1 single component
Inductance Type: Fixed Inductance Rating: 600.00 microhenries single component single winding Frequency Rating: 800.0 hertz single component Body Length: 0.600 inches Body Outside Diameter: 1.188 inches Maximum Operating Temp: 130.0 degrees celsius Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 750.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.250 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	Inductance Type: Fixed Inductance Rating: 600.00 microhenries single component single winding Frequency Rating: 800.0 hertz single component Body Length: 0.600 inches Body Outside Diameter: 1.188 inches Maximum Operating Temp: 130.0 degrees celsius Winding Quantity: 1 single component
Fixed Inductance Rating: 600.00 microhenries single component single winding Frequency Rating: 800.0 hertz single component Body Length: 0.600 inches Body Outside Diameter: 1.188 inches Maximum Operating Temp: 130.0 degrees celsius Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 750.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.250 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	Fixed Inductance Rating: 600.00 microhenries single component single winding Frequency Rating: 800.0 hertz single component Body Length: 0.600 inches Body Outside Diameter: 1.188 inches Maximum Operating Temp: 130.0 degrees celsius Winding Quantity: 1 single component
Inductance Rating: 600.00 microhenries single component single winding Frequency Rating: 800.0 hertz single component Body Length: 0.600 inches Body Outside Diameter: 1.188 inches Maximum Operating Temp: 130.0 degrees celsius Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 750.0 milliamperes dc single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	Inductance Rating: 600.00 microhenries single component single winding Frequency Rating: 800.0 hertz single component Body Length: 0.600 inches Body Outside Diameter: 1.188 inches Maximum Operating Temp: 130.0 degrees celsius Winding Quantity: 1 single component
Frequency Rating: 800.0 hertz single component Body Length: 0.600 inches Body Outside Diameter: 1.188 inches Maximum Operating Temp: 130.0 degrees celsius Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Winding Operating Current: 750.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.250 single group Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	600.00 microhenries single component single winding Frequency Rating: 800.0 hertz single component Body Length: 0.600 inches Body Outside Diameter: 1.188 inches Maximum Operating Temp: 130.0 degrees celsius Winding Quantity: 1 single component
Frequency Rating: 800.0 hertz single component  Body Length: 0.600 inches  Body Outside Diameter: 1.188 inches  Maximum Operating Temp: 130.0 degrees celsius  Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group  Mounting Method: Threaded hole single group  Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group  Thread Size: 0.138 inches single group  Winding Operating Current: 750.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 0.250 single component single winding  Thread Series Designator: Unc single group  Terminal Type And Quantity: 2 pin  Shelf Life: N/a	Frequency Rating: 800.0 hertz single component  Body Length: 0.600 inches  Body Outside Diameter: 1.188 inches  Maximum Operating Temp: 130.0 degrees celsius  Winding Quantity: 1 single component
800.0 hertz single component  Body Length: 0.600 inches  Body Outside Diameter: 1.188 inches  Maximum Operating Temp: 130.0 degrees celsius  Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group  Mounting Method: Threaded hole single group  Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group  Thread Size: 0.138 inches single group  Winding Operating Current: 750.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 0.250 single component single winding  Thread Series Designator: Unc single group  Terminal Type And Quantity: 2 pin  Shelf Life: N/a	800.0 hertz single component  Body Length: 0.600 inches  Body Outside Diameter: 1.188 inches  Maximum Operating Temp: 130.0 degrees celsius  Winding Quantity: 1 single component
Body Length:  0.600 inches  Body Outside Diameter:  1.188 inches  Maximum Operating Temp:  130.0 degrees celsius  Winding Quantity:  1 single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  1 single group  Mounting Method:  Threaded hole single group  Rating Method:  Electrical single component single winding  Thready Qty Per Inch (tpi):  32 single group  Thread Size:  0.138 inches single group  Winding Operating Current:  750.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  0.250 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	Body Length:  0.600 inches  Body Outside Diameter:  1.188 inches  Maximum Operating Temp:  130.0 degrees celsius  Winding Quantity:  1 single component
0.600 inches  Body Outside Diameter:  1.188 inches  Maximum Operating Temp:  130.0 degrees celsius  Winding Quantity:  1 single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  1 single group  Mounting Method:  Threaded hole single group  Rating Method:  Electrical single component single winding  Thready Qty Per Inch (tpi):  32 single group  Thread Size:  0.138 inches single group  Winding Operating Current:  750.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  0.250 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	0.600 inches  Body Outside Diameter:  1.188 inches  Maximum Operating Temp:  130.0 degrees celsius  Winding Quantity:  1 single component
Body Outside Diameter:  1.188 inches  Maximum Operating Temp:  130.0 degrees celsius  Winding Quantity:  1 single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  1 single group  Mounting Method:  Threaded hole single group  Rating Method:  Electrical single component single winding  Thready Qty Per Inch (tpi):  32 single group  Thread Size:  0.138 inches single group  Winding Operating Current:  750.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  0.250 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	Body Outside Diameter:  1.188 inches  Maximum Operating Temp:  130.0 degrees celsius  Winding Quantity:  1 single component
Maximum Operating Temp:  130.0 degrees celsius  Winding Quantity:  1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity:  1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 750.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.250 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	1.188 inches  Maximum Operating Temp: 130.0 degrees celsius  Winding Quantity: 1 single component
Maximum Operating Temp: 130.0 degrees celsius Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 750.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.250 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	Maximum Operating Temp: 130.0 degrees celsius Winding Quantity: 1 single component
Winding Quantity:  1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity:  1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 750.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.250 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	130.0 degrees celsius  Winding Quantity:  1 single component
Winding Quantity:  1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity:  1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 750.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.250 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	Winding Quantity: 1 single component
1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 750.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.250 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	1 single component
Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 750.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.250 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Fully enclosed  Mounting Facility Quantity:  1 single group  Mounting Method:  Threaded hole single group  Rating Method:  Electrical single component single winding  Thready Qty Per Inch (tpi):  32 single group  Thread Size:  0.138 inches single group  Winding Operating Current:  750.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  0.250 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	Inclosure Type:
Mounting Facility Quantity:  1 single group  Mounting Method: Threaded hole single group  Rating Method: Electrical single component single winding  Thready Qty Per Inch (tpi): 32 single group  Thread Size: 0.138 inches single group  Winding Operating Current: 750.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 0.250 single component single winding  Thread Series Designator: Unc single group  Terminal Type And Quantity: 2 pin  Shelf Life: N/a	
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 750.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.250 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	Fully enclosed
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 750.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.250 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	Mounting Facility Quantity:
Threaded hole single group  Rating Method: Electrical single component single winding  Thready Qty Per Inch (tpi): 32 single group  Thread Size: 0.138 inches single group  Winding Operating Current: 750.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 0.250 single component single winding  Thread Series Designator: Unc single group  Terminal Type And Quantity: 2 pin  Shelf Life: N/a	1 single group
Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 750.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.250 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	Mounting Method:
Electrical single component single winding  Thready Qty Per Inch (tpi): 32 single group  Thread Size: 0.138 inches single group  Winding Operating Current: 750.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 0.250 single component single winding  Thread Series Designator: Unc single group  Terminal Type And Quantity: 2 pin  Shelf Life: N/a	Threaded hole single group
Thready Qty Per Inch (tpi):  32 single group  Thread Size:  0.138 inches single group  Winding Operating Current:  750.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  0.250 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	Rating Method:
Thread Size:  0.138 inches single group  Winding Operating Current:  750.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  0.250 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	Electrical single component single winding
Thread Size:  0.138 inches single group  Winding Operating Current:  750.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  0.250 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	Thready Qty Per Inch (tpi):
0.138 inches single group  Winding Operating Current: 750.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 0.250 single component single winding  Thread Series Designator: Unc single group  Terminal Type And Quantity: 2 pin  Shelf Life: N/a	32 single group
Winding Operating Current: 750.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.250 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	Thread Size:
750.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  0.250 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	0.138 inches single group
Dc Resistance Rating In Ohms:  0.250 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	Winding Operating Current:
0.250 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	750.0 milliamperes dc single component single winding
Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	Dc Resistance Rating In Ohms:
Unc single group  Terminal Type And Quantity: 2 pin  Shelf Life: N/a	0.250 single component single winding
Terminal Type And Quantity: 2 pin Shelf Life: N/a	Thread Series Designator:
2 pin Shelf Life: N/a	Unc single group
Shelf Life: N/a	Terminal Type And Quantity:
N/a	2 pin
	Shelf Life:
Unit Of Measure:	N/a
_	Unit Of Measure:
Demilitarization:	Demilitarization:

No

## NSN 5950-00-264-5583

Reactor - Page 2 of 2



Fiig:

A058b0