NSN 5950-00-265-0544

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-265-0544

eliability Indicator:	
lot established	
enter To Center Distance Between Mounting Facilities Parallel Te	o Length:
.875 inches single mounting facility single center group	
enter To Center Distance Between Mounting Facilities Parallel Te	o Width:
.750 inches single mounting facility single center group	
requency Rating:	
0.0 hertz single component or 60.0 hertz single component	
nput-output Phase Relationship:	
ingle phase to single phase single component	
Vinding Shielding Method:	
nternal shield grounded to inclosure single component	
ody Length:	
.312 inches	
ody Width:	
.125 inches	
ody Height:	
.438 inches	
nclosure Type:	
lermetically sealed	
Iounting Facility Quantity:	
single group	
Iounting Method:	
Inthreaded hole single group	
Vinding Function And Quantity:	
primary single component and 1 secondary single component	
Vinding Operating Current:	
.0 amperes ac single component single secondary	
Vinding Operating Voltage:	
.00 ac volts single component single secondary	
erminal Type And Quantity:	
tab, solder lug	
helf Life:	
l/a	
nit Of Measure:	
emilitarization:	
lo	
iig:	
058b0	