NSN 5950-00-266-8939

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-266-8939
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.062 inches single mounting facility single center group
Frequency Rating:
380.0 hertz single component and 1.6 kilohertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Body Length:
4.625 inches
Body Width:
3.625 inches
Body Height:
3.000 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 2 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.164 inches single group
Winding Operating Voltage:
1.30 ac kilovolts single component 1st secondary95.00 ac volts single component 2nd secondary and 280.00 ac volts single component
2nd secondary and 510.00 ac volts single component 2nd secondary and 890.00 ac volts single component 2nd secondary and 1.10 ac
kilovolts single component 2nd secondary and 1.30 ac kilovolts single component 2nd secondary and 1.40 ac kilovolts single component
2nd secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
14 tab, solder lug
Shelf Life:
N/a

Nic

Unit Of Measure:

Demilitarization:

NSN 5950-00-266-8939

Power Transformer - Page 2 of 2



Fiig:

A058b0