

View Online at <https://aerobasegroup.com/nsn/5950-00-266-8939>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.062 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 1.6 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

4.625 inches

Body Width:

3.625 inches

Body Height:

3.000 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Voltage:

1.30 ac kilovolts single component 1st secondary 95.00 ac volts single component 2nd secondary and 280.00 ac volts single component 2nd secondary and 510.00 ac volts single component 2nd secondary and 890.00 ac volts single component 2nd secondary and 1.10 ac kilovolts single component 2nd secondary and 1.30 ac kilovolts single component 2nd secondary and 1.40 ac kilovolts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0