

View Online at <https://aerobasegroup.com/nsn/5950-00-269-2830>

Reliability Indicator:

Not established

Frequency Rating:

380.0 hertz single component and 1.5 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 1.500 inches and 1.625 inches

Body Width:

Between 1.500 inches and 1.625 inches

Body Height:

Between 2.250 inches and 2.375 inches

Distance Between Mounting Facility Centers:

1.688 inches single mounting facility single center group

End Application:

Engine, aircraft t-56

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

860.0 milliamperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

105.00 ac volts single component single primary and 6.30 ac volts single component single secondary 115.00 ac volts single component single primary and 125.00 ac volts single component single primary and 135.00 ac volts single component single primary

Special Features:

Weapon system essential

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0