

View Online at <https://aerobasegroup.com/nsn/5950-00-269-9674>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.812 inches single mounting facility single center group

Overall Height:

4.656 inches

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

Between 4.940 inches and 5.015 inches

Body Width:

Between 4.752 inches and 4.827 inches

Body Height:

4.031 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Criticality Code Justification:

Zzzy

Winding Operating Voltage:

38.00 ac volts single component 2nd secondary 115.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 solder stud

Reference Number Differentiating Characteristics:

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0