

View Online at <https://aerobasegroup.com/nsn/5950-00-270-1116>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Overall Width:

2.400 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

2.810 inches

Body Width:

2.250 inches

Body Height:

1.500 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

41.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

222.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

15 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0