# NSN 5950-00-272-7334

Pulse Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-272-7334

# **Reliability Indicator:**

Not established

#### **Hazardous Locations/environmental Protection:**

Vibration resistant

# Center To Center Distance Between Mounting Facilities Parallel To Length:

1.688 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.360 inches single mounting facility single center group

#### **Mounting Hole Diameter:**

0.124 inches single group and 0.129 inches single group

#### **Inductance Rating:**

2.25 microhenries single component single primary

#### Frequency Rating:

1.0 kilohertz single component and 310.0 kilohertz single component

#### **Pulse Repetition Rate:**

20.0 kilohertz single component

### Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

# **Body Length:**

2.120 inches

# **Body Width:**

1.740 inches

#### **Body Height:**

1.340 inches

# **Inclosure Type:**

Open

# **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Flange single group and unthreaded hole single group

# Winding Function And Quantity:

1 primary single component and 2 secondary single component

# Dc Resistance Rating In Ohms:

1.400 single component single primary

# **Terminal Type And Quantity:**

8 turret

#### Shelf Life:

N/a

# **Unit Of Measure:**

--

#### **Demilitarization:**

No

# NSN 5950-00-272-7334

Pulse Transformer - Page 2 of 2



Fiig:

A058b0