

View Online at <https://aerobasegroup.com/nsn/5950-00-273-3960>

**Reliability Indicator:**

Not establishednot established

**Overall Length:**

4.875 inches 4.875 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.875 inches single mounting facility single center group3.875 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group

**Overall Height:**

6.500 inches 6.500 inches

**Overall Width:**

3.125 inches 3.125 inches

**Mounting Hole Diameter:**

0.188 inches single group0.188 inches single group

**Frequency Rating:**

380.0 hertz single component and 380.0 hertz single component and 420.0 hertz single component420.0 hertz single component

**Input-output Phase Relationship:**

Three phase to six phase single component and three phase to six phase single component and three phase to three phase single componentthree phase to three phase single component

**Transformer Winding Connection Type:**

Wye-delta-wyewye-delta-wye

**Winding Shielding Method:**

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

**Maximum Operating Temp:**

155.0 degrees celsius155.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Unthreaded hole single groupunthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 11 secondary single component11 secondary single component

**Winding Operating Current:**

7.0 amperes dc single component 4th secondary

**Winding Power Rating:**

76.8 volts-amperes single component 3rd secondary12.9 volts-amperes single component 2nd secondary

**Winding Operating Voltage:**

31.20 ac volts single component 1st secondary and 32.80 ac volts single component 1st secondary

**Special Features:**

One primary and eleven secondaries

**Terminal Type And Quantity:**

16 tab, solder lug and 49 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0