

View Online at <https://aerobasegroup.com/nsn/5950-00-273-3960>

Reliability Indicator:

Not establishednot established

Overall Length:

4.875 inches 4.875 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.875 inches single mounting facility single center group3.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group

Overall Height:

6.500 inches 6.500 inches

Overall Width:

3.125 inches 3.125 inches

Mounting Hole Diameter:

0.188 inches single group0.188 inches single group

Frequency Rating:

380.0 hertz single component and 380.0 hertz single component and 420.0 hertz single component420.0 hertz single component

Input-output Phase Relationship:

Three phase to six phase single component and three phase to six phase single component and three phase to three phase single componentthree phase to three phase single component

Transformer Winding Connection Type:

Wye-delta-wyewye-delta-wye

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

Maximum Operating Temp:

155.0 degrees celsius155.0 degrees celsius

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 11 secondary single component11 secondary single component

Winding Operating Current:

7.0 amperes dc single component 4th secondary

Winding Power Rating:

76.8 volts-amperes single component 3rd secondary12.9 volts-amperes single component 2nd secondary

Winding Operating Voltage:

31.20 ac volts single component 1st secondary and 32.80 ac volts single component 1st secondary

Special Features:

One primary and eleven secondaries

Terminal Type And Quantity:

16 tab, solder lug and 49 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0