NSN 5950-00-276-5191

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-276-5191

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.000 inches all mounting facilities all center groupings |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.375 inches all mounting facilities all center groupings |
| Overall Height: |
| 2.040 inches |
| Overall Width: |
| 1.880 inches |
| Frequency Rating: |
| 380.0 hertz single component and 400.0 hertz single component |
| nput-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| nternal shield brought out to terminal single component |
| Body Length: |
| 2.480 inches |
| nclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 2 all groupings |
| Mounting Method: |
| Threaded stud all groupings |
| Winding Function And Quantity: |
| 1 primary single component and 4 secondary single component |
| Features Provided: |
| Color coded lead |
| Thread Size: |
| 0.138 inches all groupings |
| Winding Operating Voltage: |
| 62.00 ac volts single component 1st secondary33.40 ac volts single component 3rd secondary15.00 ac volts single component 2nd |
| secondary |
| Thread Series Designator: |
| Jnc all groupings |
| Terminal Type And Quantity: |
| 15 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |

No

NSN 5950-00-276-5191

Power Transformer - Page 2 of 2



Fiig:

A058b0