

View Online at <https://aerobasegroup.com/nsn/5950-00-276-5448>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility single center group2.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

Mounting Slot Width:

0.125 inches single group and 0.125 inches single group and 0.187 inches single group0.187 inches single group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single componentthree phase to three phase single component

Transformer Winding Connection Type:

Delta-delta and delta-delta and delta-wyedelta-wye

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

Body Length:

3.000 inches 3.000 inches

Body Width:

2.750 inches 2.750 inches

Body Height:

Between 3.875 inches and 3.875 inches and 4.125 inches 4.125 inches

Maximum Operating Temp:

170.0 degrees celsius170.0 degrees celsius

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Slot single groupslot single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 11 secondary single component11 secondary single component

Winding Operating Current:

200.0 milliamperes dc single component 4th secondary

Winding Operating Voltage:

180.00 ac volts single component single primary and 180.00 ac volts single component single primary and 200.00 ac volts single component single primary and 200.00 ac volts single component single primary and 220.00 ac volts single component single primary220.00 ac volts single component single primary

Special Features:

One primary winding; eleven secondary windings, neutral tap on first through ninth secondariesone primary winding; eleven secondary windings, neutral tap on first through ninth secondaries

Terminal Type And Quantity:

1 connector, plug and 43 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0