

View Online at <https://aerobasegroup.com/nsn/5950-00-276-5484>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

**Overall Height:**

3.640 inches 3.640 inches

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single componentthree phase to three phase single component

**Transformer Winding Connection Type:**

Delta-deltadelta-delta

**Body Length:**

2.500 inches 2.500 inches

**Body Width:**

1.625 inches 1.625 inches

**Body Height:**

3.250 inches 3.250 inches

**Maximum Operating Temp:**

85.0 degrees celsius85.0 degrees celsius

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 4 secondary single component4 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group32 single group

**Thread Size:**

0.138 inches single group0.138 inches single group

**Winding Operating Current:**

300.0 milliamperes dc single component 3rd secondary

**Winding Operating Voltage:**

20.00 ac volts single component 3rd secondary115.00 ac volts single component single primary29.80 ac volts single component 4th secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

16 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0