

View Online at <https://aerobasegroup.com/nsn/5950-00-279-4018>

**Reliability Indicator:**

Not establishednot established

**Overall Length:**

3.940 inches 3.940 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.970 inches single mounting facility single center group and 2.970 inches single mounting facility single center group and 3.030 inches single mounting facility single center group3.030 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.350 inches single mounting facility single center group and 1.350 inches single mounting facility single center group and 1.410 inches single mounting facility single center group1.410 inches single mounting facility single center group

**Overall Width:**

2.120 inches 2.120 inches

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Three phase to single phase single component and three phase to single phase single component and three phase to three phase single componentthree phase to three phase single component

**Transformer Winding Connection Type:**

Wye-wyewye-wye

**Winding Shielding Method:**

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

**Body Length:**

3.940 inches 3.940 inches

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 9 secondary single component9 secondary single component

**Thread Size:**

0.164 inches single group0.164 inches single group

**Winding Operating Current:**

300.0 milliamperes dc single component 4th secondary

**Winding Operating Voltage:**

552.00 ac volts single component 1st secondary236.00 ac volts single component 3rd secondary236.00 ac volts single component 2nd secondary

**Special Features:**

1 primary winding; 9 secondary windings

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

27 standoff, solder lug

**Shelf Life:**

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0