

View Online at <https://aerobasegroup.com/nsn/5950-00-279-4018>

Reliability Indicator:

Not establishednot established

Overall Length:

3.940 inches 3.940 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.970 inches single mounting facility single center group and 2.970 inches single mounting facility single center group and 3.030 inches single mounting facility single center group3.030 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.350 inches single mounting facility single center group and 1.350 inches single mounting facility single center group and 1.410 inches single mounting facility single center group1.410 inches single mounting facility single center group

Overall Width:

2.120 inches 2.120 inches

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component and three phase to single phase single component and three phase to three phase single componentthree phase to three phase single component

Transformer Winding Connection Type:

Wye-wyewye-wye

Winding Shielding Method:

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

Body Length:

3.940 inches 3.940 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 9 secondary single component9 secondary single component

Thread Size:

0.164 inches single group0.164 inches single group

Winding Operating Current:

300.0 milliamperes dc single component 4th secondary

Winding Operating Voltage:

552.00 ac volts single component 1st secondary236.00 ac volts single component 3rd secondary236.00 ac volts single component 2nd secondary

Special Features:

1 primary winding; 9 secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

27 standoff, solder lug

Shelf Life:

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0