NSN 5950-00-279-7023

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-279-7023

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.688 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.500 inches single mounting facility single center group |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 1500.00 henry single component single winding |
| Frequency Rating: |
| 50.0 hertz single component |
| Body Length: |
| 0.969 inches |
| Body Width: |
| 0.781 inches |
| Body Height: |
| 1.406 inches |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Rating Method: |
| Electrical single component single winding |
| Thready Qty Per Inch (tpi): |
| 40 single group |
| Thread Size: |
| 0.112 inches single group |
| Dc Resistance Rating In Ohms: |
| 38000.000 single component single winding |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 4 wire hook |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5950-00-279-7023

Reactor - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A058b0