

View Online at <https://aerobasegroup.com/nsn/5950-00-280-4507>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility single center group2.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.188 inches single mounting facility single center group2.188 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

3.000 inches 3.000 inches

Body Width:

2.875 inches 2.875 inches

Body Height:

4.500 inches 4.500 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.190 inches single group0.190 inches single group

Winding Operating Current:

6.0 amperes ac single component 2nd secondary

Winding Operating Voltage:

5.00 ac volts single component 2nd secondary2.50 ac volts single component 1st secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

7 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0