

View Online at <https://aerobasegroup.com/nsn/5950-00-280-4546>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.750 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.000 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component and 1.6 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

5.125 inches

**Body Width:**

4.375 inches

**Body Height:**

5.500 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thready Qty Per Inch (tpi):**

20 single group

**Thread Size:**

0.250 inches single group

**Winding Operating Voltage:**

620.00 ac volts single component 2nd secondary 103.50 ac volts single component single primary and 115.00 ac volts single component single primary and 126.50 ac volts single component single primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

10 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0