

View Online at <https://aerobasegroup.com/nsn/5950-00-280-4561>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

9.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.938 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

13.375 inches

Body Width:

11.375 inches

Body Height:

8.750 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Power Rating:

600.0 volts-amperes single component single secondary

Winding Operating Voltage:

115.00 ac pounds per hour wet single component single secondary

Test Data Document:

81349-mil-t-16315 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 tab, solder lug

Specification Or Standard:

Tf type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0