

View Online at <https://aerobasegroup.com/nsn/5950-00-280-4607>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.375 inches single mounting facility single center group1.375 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.250 inches single mounting facility single center group1.250 inches single mounting facility single center group

**Overall Height:**

2.813 inches 2.813 inches

**Frequency Rating:**

380.0 hertz single component and 380.0 hertz single component and 1.5 kilohertz single component1.5 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Maximum Transformer Power Rating:**

32.6 volt-ampere single component32.6 volt-ampere single component

**Body Length:**

1.938 inches 1.938 inches

**Body Width:**

1.813 inches 1.813 inches

**Body Height:**

2.438 inches 2.438 inches

**Maximum Operating Temp:**

105.0 degrees celsius105.0 degrees celsius

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

**Thread Size:**

0.138 inches single group0.138 inches single group

**Winding Operating Current:**

40.0 milliamperes ac single component 1st secondary

**Winding Power Rating:**

6.3 volts-amperes single component 3rd secondary20.0 volts-amperes single component 1st secondary

**Winding Operating Voltage:**

6.30 ac volts single component 2nd secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

10 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0