

View Online at <https://aerobasegroup.com/nsn/5950-00-280-4607>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group1.250 inches single mounting facility single center group

Overall Height:

2.813 inches 2.813 inches

Frequency Rating:

380.0 hertz single component and 380.0 hertz single component and 1.5 kilohertz single component1.5 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Maximum Transformer Power Rating:

32.6 volt-ampere single component32.6 volt-ampere single component

Body Length:

1.938 inches 1.938 inches

Body Width:

1.813 inches 1.813 inches

Body Height:

2.438 inches 2.438 inches

Maximum Operating Temp:

105.0 degrees celsius105.0 degrees celsius

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Current:

40.0 milliamperes ac single component 1st secondary

Winding Power Rating:

6.3 volts-amperes single component 3rd secondary20.0 volts-amperes single component 1st secondary

Winding Operating Voltage:

6.30 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0