

View Online at <https://aerobasegroup.com/nsn/5950-00-280-4609>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.125 inches single mounting facility single center group1.125 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.625 inches single mounting facility single center group1.625 inches single mounting facility single center group

**Frequency Rating:**

380.0 hertz single component and 380.0 hertz single component and 420.0 hertz single component420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and brought out to terminal single componentinternal shield grounded to inclosure and brought out to terminal single component

**Body Length:**

2.062 inches 2.062 inches

**Body Width:**

1.938 inches 1.938 inches

**Body Height:**

1.688 inches 1.688 inches

**Inclosure Type:**

Openopen

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

**Thread Size:**

0.112 inches single group0.112 inches single group

**Winding Operating Current:**

400.0 milliamperes ac single component 2nd secondary

**Winding Operating Voltage:**

24.00 ac volts single component 2nd secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

10 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0