## NSN 5950-00-280-4663

Audio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-280-4663

## **Reliability Indicator:**

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

0.938 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

0.875 inches single mounting facility single center group

## Impedance Rating In Ohms:

0.7 single component single secondary

## Frequency Rating:

20.0 hertz single component and 10.0 kilohertz single component

### **Primary To Secondary Turn Ratio:**

1 to 230 single component

### **Winding Shielding Method:**

Internal shield grounded to inclosure single component

### **Body Length:**

1.531 inches

### **Body Width:**

1.422 inches

## **Body Height:**

2.000 inches

## Inclosure Type:

Hermetically sealed

## **Mounting Facility Quantity:**

4 single group

## **Mounting Method:**

Threaded stud single group

## **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

## Thready Qty Per Inch (tpi):

32 single group

## **Thread Size:**

0.138 inches single group

## **Winding Operating Current:**

2.0 milliamperes dc single component single primary

### **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

5 tab, solder lug

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5950-00-280-4663

Audio Frequency Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0