

View Online at <https://aerobasegroup.com/nsn/5950-00-280-5590>

**Reliability Indicator:**

Not establishednot established

**Overall Length:**

2.861 inches 2.861 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.875 inches single mounting facility single center group1.875 inches single mounting facility single center group

**Overall Height:**

2.742 inches 2.742 inches

**Overall Width:**

4.554 inches 4.554 inches

**Frequency Rating:**

50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Body Length:**

2.861 inches 2.861 inches

**Body Width:**

2.711 inches 2.711 inches

**Body Height:**

3.742 inches 3.742 inches

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group32 single group

**Thread Size:**

0.164 inches single group0.164 inches single group

**Winding Operating Current:**

40.0 milliamperes ac single component 2nd secondary

**Winding Operating Voltage:**

6.30 ac volts single component 1st secondary117.00 ac volts single component single primary450.00 ac volts single component 2nd secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

10 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0