

View Online at <https://aerobasegroup.com/nsn/5950-00-280-5590>

Reliability Indicator:

Not establishednot established

Overall Length:

2.861 inches 2.861 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.875 inches single mounting facility single center group1.875 inches single mounting facility single center group

Overall Height:

2.742 inches 2.742 inches

Overall Width:

4.554 inches 4.554 inches

Frequency Rating:

50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

2.861 inches 2.861 inches

Body Width:

2.711 inches 2.711 inches

Body Height:

3.742 inches 3.742 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.164 inches single group0.164 inches single group

Winding Operating Current:

40.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

6.30 ac volts single component 1st secondary117.00 ac volts single component single primary450.00 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0