

View Online at <https://aerobasegroup.com/nsn/5950-00-280-5738>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches single mounting facility single center group3.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

5.312 inches 5.312 inches

Body Width:

4.719 inches 4.719 inches

Body Height:

6.062 inches 6.062 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thready Qty Per Inch (tpi):

24 single group24 single group

Thread Size:

0.216 inches single group0.216 inches single group

Winding Operating Current:

7.5 amperes ac single component single secondary

Winding Operating Voltage:

95.00 ac volts single component single primary and 28.00 ac volts single component single secondary105.00 ac volts single component single primary and 115.00 ac volts single component single primary and 125.00 ac volts single component single primary and 135.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0