

View Online at <https://aerobasegroup.com/nsn/5950-00-283-3149>

Reliability Indicator:

Not establishednot established

Frequency Rating:

50.0 hertz single component and 50.0 hertz single component and 60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

Body Length:

2.188 inches 2.188 inches

Body Width:

2.062 inches 2.062 inches

Body Height:

2.188 inches 2.188 inches

Distance Between Mounting Facility Centers:

2.062 inches single mounting facility single center group2.062 inches single mounting facility single center group

End Application:

Approach light system (als)approach light system (als)

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.164 inches single group0.164 inches single group

Winding Operating Current:

120.0 milliamperes ac single component single secondary

Winding Operating Voltage:

110.00 ac volts single component single primary and 95.00 ac volts single component single secondary120.00 ac volts single component single primary and 130.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0