

View Online at <https://aerobasegroup.com/nsn/5950-00-283-3149>

**Reliability Indicator:**

Not establishednot established

**Frequency Rating:**

50.0 hertz single component and 50.0 hertz single component and 60.0 hertz single component60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

**Body Length:**

2.188 inches 2.188 inches

**Body Width:**

2.062 inches 2.062 inches

**Body Height:**

2.188 inches 2.188 inches

**Distance Between Mounting Facility Centers:**

2.062 inches single mounting facility single center group2.062 inches single mounting facility single center group

**End Application:**

Approach light system (als)approach light system (als)

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

2 single group2 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group32 single group

**Thread Size:**

0.164 inches single group0.164 inches single group

**Winding Operating Current:**

120.0 milliamperes ac single component single secondary

**Winding Operating Voltage:**

110.00 ac volts single component single primary and 95.00 ac volts single component single secondary120.00 ac volts single component single primary and 130.00 ac volts single component single primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

6 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0