# NSN 5950-00-284-4194

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-284-4194

### **Reliability Indicator:**

Not establishednot established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group1.750 inches single mounting facility single center group

#### Frequency Rating:

60.0 hertz single component60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

#### Body Length:

2.875 inches 2.875 inches

#### Body Width:

2.500 inches 2.500 inches

#### Body Height:

4.250 inches 4.250 inches

#### Inclosure Type:

Fully enclosedfully enclosed

# Mounting Facility Quantity:

4 single group4 single group

# Mounting Method:

Threaded stud single groupthreaded stud single group

# Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

# Thready Qty Per Inch (tpi):

32 single group32 single group

# Thread Size:

0.190 inches single group0.190 inches single group

# Winding Operating Current:

200.0 milliamperes ac single component 2nd secondary

# Winding Operating Voltage:

6.30 ac volts single component 1st secondary

#### Thread Series Designator:

Unf single group

# Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

# NSN 5950-00-284-4194

Power Transformer - Page 2 of 2

**Fiig:** A058b0

